

Information and updates from KE2 Therm Solutions

Now Available! KE2 Evap v4.0 with Smart Access

Smart Access provides quick and easy, real time access, to your refrigeration systems 24/7. No port forwarding. No vpn.

3 easy steps.

- 1 Enable Smart Access in the Introduction Mode menu**
 ■ After setting Room Temp, Defrost Type & Valve Type, set Smart Access to **Enabled**.
- 2 Go to smartaccess.ke2therm.net**
 ■ Using your PC, tablet or smartphone, enter <http://smartaccess.ke2therm.net> in the web browser's address bar.
- 3 Enter default information**
 ■ Enter default information, and click **Log In** button.
Site: installer **Password:** controller's Mac Address

Now it's easier than ever to monitor and adjust your KE2 Evaps remotely. New, KE2 Evap version 4.0 firmware includes Smart Access.

All the KE2 Evap needs is a physical connection to the network router, then follow the 3 steps.

Smart Access automatically connects to your personal web portal, providing a "customized" dashboard of all the KE2 Evaps you setup with Smart Access.

For more information, contact KE2 Therm and request bulletin A.1.76.

and you are there!

Ex: Joe's Portal
 dashboard of all Joe's KE2 Evap controllers connected through Smart Access

Location	Mode	Room	SH Superheat	Alarm
Joe's Bar Walk-in Freezer	Off	-8.2	8.7 F	All Clear
Joe's Bar Walk-in Cooler	Refrigerate	36.1	10.6 F	All Clear
Joe's Corner Mkt - Beer Cave	Refrigerate	33.5	9.2 F	All Clear
Joe's Corner Mkt Walkin Freezer	Off	-10.3	6.8 F	All Clear

Now Available!

KE2 Evap Supermarket Retrofit Kit pn 21096

The KE2 Evap Supermarket Retrofit kit is a complete package for upgrading walk-ins, and refrigerated rooms, to improve the operating environment.

The KE2 Evap is proven to reduce or eliminate icing issues, provides remote monitoring and control, and is third party verified as an energy saving controller.

For more information, contact KE2 Therm and request bulletin A.1.74.

Supermarket Retrofit Kit Contents:

- A KE2 Evaporator Efficiency** includes KE2 Evap controller, mounting hardware, screw down terminals, voltage jumpers and air sensor mount
- B Mounting Box**
40 mil embossed aluminum
- C KE2 Wire Harness**
9-wire, 10 ft. harness with appropriate gauge wires and connections for controller
- D Heavy Duty Door Switch**
24" stainless steel armored cable, hermetically sealed reed switch
- E Ethernet Adaptor Kit**

NEW!

